

Sprays] T-Spray™

The Senninger T-Spray delivers a fine spray ideal for delicate stock. It can be mounted upright or inverted and is also available in a high angle model for upright installations only.



FEATURES:

- 360° Spray nozzle
- No moving parts for longer life
- High-angle upright T-stem provides larger diameter of coverage
- Removable T-stem for easy cleaning
- Flow rates: 0.98 to 2.85 gpm [223 to 647 L/hr]
- Operating pressures: 15 to 40 psi [1.03 to 2.76 bar]
- Inlet: 1/2" M NPT male
- Two-year warranty on materials, workmanship and performance
- Color-coded stems for easy size identification



Standard Angle for upright or inverted installations

Sprinkler Base Pressure [psi]	15	20	25	30	35	40	[bar]	1.03	1.38	1.72	2.07	2.41	2.76
#6 Nozzle - Gold [3/32"]							#6 Nozzle - Gold [2.38mm]						
Flow [gpm]	0.98	1.14	1.27	1.40	1.52	1.63	Flow [L/hr]	223	259	288	318	345	370
Diam. at 1.5' ht. [ft.]	15.5	17.0	18.0	19.0	20.0	21.0	Diam. at 0.46m ht. [m]	4.7	5.2	5.5	5.8	6.1	6.4
Diam. at 3.0' ht. [ft.]	17.5	18.5	19.5	20.5	21.5	22.0	Diam. at .092m ht. [m]	5.3	5.6	5.9	6.3	6.6	6.7
#7 Nozzle - Lime [7/64"]							#7 Nozzle - Lime [2.78mm]						
Flow [gpm]	1.34	1.56	1.73	1.90	2.05	2.20	Flow [L/hr]	304	354	393	432	466	500
Diam. at 1.5' ht. [ft.]	17.0	18.5	19.5	20.5	21.0	21.5	Diam. at 0.46m ht. [m]	5.2	5.6	5.9	6.3	6.4	6.6
Diam. at 3.0' ht. [ft.]	18.5	19.5	20.5	21.5	22.5	23.0	Diam. at .092m ht. [m]	5.6	5.9	6.3	6.6	6.9	7.0
#8 Nozzle - Lavender [1/8"]							#8 Nozzle - Lavender [3.18mm]						
Flow [gpm]	1.73	2.01	2.23	2.45	2.65	2.85	Flow [L/hr]	393	457	506	556	602	647
Diam. at 1.5' ht. [ft.]	18.0	19.5	20.5	21.0	21.5	22.0	Diam. at 0.46m ht. [m]	5.5	5.9	6.3	6.4	6.6	6.7
Diam. at 3.0' ht. [ft.]	19.0	20.0	21.0	22.0	23.0	23.5	Diam. at .092m ht. [m]	5.8	6.1	6.4	6.7	7.0	7.2

High Angle for upright installations

Sprinkler Base Pressure [psi]	15	20	25	30	35	40	[bar]	1.03	1.38	1.72	2.07	2.41	2.76
#8 Nozzle - Dark Lavender [1/8"]							#8 Nozzle - Dark Lavender [3.18mm]						
Flow [gpm]	1.73	2.01	2.23	2.45	2.65	2.85	Flow [L/hr]	393	457	506	556	602	647
Diam. at 1.5' ht. [ft.]	25.5	27.5	29.0	30.0	31.0	32.0	Diam. at 0.46m ht. [m]	7.8	8.4	8.8	9.2	9.5	9.8

Sprinkler performance may vary with actual field conditions. Minimum recommended riser height is 1.5ft. [0.46 m].