

Sprays] T-Spray™

The Senninger T-Spray delivers a fine spray – ideal for delicate stock. It can be mounted upright or inverted and is also available in a high angle model for upright installations only.



FEATURES:

- 360° Spray nozzle.
- No moving parts for longer life
- High-angle upright T-stem provides larger diameter of coverage
- Removable T-stem for easy cleaning
- Color-coded stems for easy size identification
- Flow rates: 0.98 to 2.85 gpm [216 to 684 L/hr]
- Operating pressures: 15 to 40 psi [1.0 to 3.0 bar]
- Inlet: 1/2" M NPT male
- Two-year warranty on materials, workmanship AND performance



Standard Angle for upright or inverted installations

U.S. Data							Metric Data					
Sprinkler Base Press. [psi]	15	20	25	30	35	40	[bar]	1.0	1.5	2.0	2.5	3.0
							[psi]	14.50	21.75	29.00	36.25	43.50
#6 Nozzle - Gold [3/32"]							#6 Nozzle - Gold [2.38mm]					
Flow [gpm]	0.98	1.14	1.27	1.40	1.52	1.63	Flow [L/hr]	216	288	324	360	396
Diam. at 1.5' ht. [ft.]	15.5	17.0	18.0	19.0	20.0	21.0	Diam. at 0.5m ht. [m]	4.7	5.3	5.7	6.2	6.5
Diam. at 3.0' ht. [ft.]	17.5	18.5	19.5	20.5	21.5	22.0	Diam. at 1.0m ht. [m]	5.3	5.7	6.2	6.6	6.8
#7 Nozzle - Lime [7/64"]							#7 Nozzle - Lime [2.78mm]					
Flow [gpm]	1.34	1.56	1.73	1.90	2.05	2.20	Flow [L/hr]	288	360	432	468	540
Diam. at 1.5' ht. [ft.]	17.0	18.5	19.5	20.5	21.0	21.5	Diam. at 0.5m ht. [m]	5.1	5.7	6.2	6.4	6.7
Diam. at 3.0' ht. [ft.]	18.5	19.5	20.5	21.5	22.5	23.0	Diam. at 1.0m ht. [m]	5.6	6.0	6.5	6.9	7.1
#8 Nozzle - Lavender [1/8"]							#8 Nozzle - Lavender [3.18mm]					
Flow [gpm]	1.73	2.01	2.23	2.45	2.65	2.85	Flow [L/hr]	396	468	540	612	684
Diam. at 1.5' ht. [ft.]	18.0	19.5	20.5	21.0	21.5	22.0	Diam. at 0.5m ht. [m]	5.4	6.0	6.4	6.6	6.8
Diam. at 3.0' ht. [ft.]	19.0	20.0	21.0	22.0	23.0	23.5	Diam. at 1.0m ht. [m]	5.7	6.2	6.6	7.0	7.3

High Angle for upright installations

U.S. Data							Metric Data					
Sprinkler Base Press. [psi]	15	20	25	30	35	40	[bar]	1.0	1.5	2.0	2.5	3.0
							[psi]	14.50	21.75	29.00	36.25	43.50
#8 Nozzle - Lavender [1/8"]							#8 Nozzle - Lavender [3.18mm]					
Flow [gpm]	1.73	2.01	2.23	2.45	2.65	2.85	Flow [L/hr]	396	468	540	612	684
Diam. at 1.5' ht. [ft.]	25.5	27.5	29.0	30.0	31.0	32.0	Diam. at 0.5m ht. [m]	7.7	8.5	9.1	9.5	9.9

Sprinkler performance may vary with actual field conditions. Other nozzle sizes are available; consult factory for specific performance data. Minimum recommended riser height is 1.5 ft. (0.46 m).