

AGRICULTURAL IRRIGATION | A Hunter Industries Company  
LOW PRESSURE - HIGH PERFORMANCE™



- 01 **Convenient:** Combines filtration and pressure regulation
- 02 **Quality:** Field proven PSR™2 components
- 03 **Durability:** Stainless-steel mesh screen
- 04 **Models:** Four pressures of 6, 10, 15, and 20 psi (0.41, 0.69, 1.03, and 1.38 bar)

## FILTER REGULATOR FOR IRRIGATION

*The Filter Regulator combines filtration and pressure regulation into one device for installation convenience*

Senninger® black and white pressure regulators are renowned for their accuracy, durability, and ability to maintain consistent outlet pressure with varying inlet pressure. Combining that performance with reduced nozzle clogging provides a solution for overall efficiency of an irrigation system.



# FILTER REGULATOR FEATURES AND FILTER SPECIFICATIONS

## FEATURES

- Quality field proven PSR™2 internal components
- Pressure models available: 6, 10, 15, and 20 psi (0.41, 0.69, 1.03, and 1.38 bar)
- Easy access to mesh screens with a twist of the bonnet; no tools required
- Convenient installation, 3/4" M NPT inlet x 3/4" F NPT outlet
- Outer dimensions: 6 1/4" L x 2 3/4" W x 7" W
- Two-year warranty on materials, workmanship, and performance

## FILTER SCREENS

- Replacement filter screens also available with color-coded rubber seals to readily identify mesh size.

Screen Models	Description
FPSR220SCREEN	Filter PSR2, 20 mesh (841 microns), <b>black</b>
FPSR230SCREEN	Filter PSR2, 30 mesh (595 microns), <b>green</b>
FPSR240SCREEN	Filter PSR2, 40 mesh (400 microns), <b>grey</b>
FPSR2120SCREEN	Filter PSR2, 120 mesh (125 microns), <b>red</b>
FPSR2140SCREEN	Filter PSR2, 140 mesh (105 microns), <b>blue</b>

FILTER REGULATOR MODELS	Description	Mesh Orifice (microns)	UP3 Nozzle Numbers	Preset Outlet Pressure	Maximum Inlet Pressure
FPSR2063M3F20	6 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>20 mesh screen</b>	841	#13 - #26	6 psi (0.41 bar)	80 psi (5.51 bar)
FPSR2063M3F30	6 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>30 mesh screen</b>	595	#6 - #12.5		
FPSR2063M3F40	6 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>40 mesh screen</b>	400	#2 - #5.5		
FPSR2103M3F20	10 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>20 mesh screen</b>	841	#13 - #26	10 psi (0.69 bar)	90 psi (6.20 bar)
FPSR2103M3F30	10 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>30 mesh screen</b>	595	#6 - #12.5		
FPSR2103M3F40	10 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>40 mesh screen</b>	400	#2 - #5.5		
FPSR2153M3F20	15 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>20 mesh screen</b>	841	#13 - #26	15 psi (1.03 bar)	95 psi (6.55 bar)
FPSR2153M3F30	15 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>30 mesh screen</b>	595	#6 - #12.5		
FPSR2153M3F40	15 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>40 mesh screen</b>	400	#2 - #5.5		
FPSR2203M3F20	20 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>20 mesh screen</b>	841	#13 - #26	20 psi (1.38 bar)	100 psi (6.89 bar)
FPSR2203M3F30	20 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>30 mesh screen</b>	595	#6 - #12.5		
FPSR2203M3F40	20 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>40 mesh screen</b>	400	#2 - #5.5		
FPSR2103M3F120	10 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>120 mesh screen</b>	125	0.5 - 15 gpm (114 - 3407 L/hr)	10 psi (0.69 bar)	90 psi (6.20 bar)
FPSR2103M3F140	10 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>140 mesh screen</b>	105			
FPSR2153M3F120	15 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>120 mesh screen</b>	125	0.5 - 15 gpm (114 - 3407 L/hr)	15 psi (1.03 bar)	95 psi (6.55 bar)
FPSR2153M3F140	15 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>140 mesh screen</b>	105			
FPSR2203M3F120	20 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>120 mesh screen</b>	125	0.5 - 15 gpm (114 - 3407 L/hr)	20 psi (1.38 bar)	100 psi (6.89 bar)
FPSR2203M3F140	20 psi, Filter PSR2, 3/4" M NPT x 3/4" F NPT, <b>140 mesh screen</b>	105			

The pressure regulator shall maintain the predetermined operating pressure provided that the inlet pressure is at least 5 psi (0.34 bar) above the expected outlet pressure, with flows up to 11 gpm (2498 L/hr), but not exceeding the maximum inlet pressure as shown above. Higher flows require additional inlet pressure to engage the regulator. Where flows are greater than 11 gpm (2498 L/hr), the inlet pressure should be at least 9 psi (0.62 bar) above the expected outlet pressure but not exceeding the maximum inlet pressure as shown above.

Pressure regulators should always be installed downstream of all shut-off valves.

Recommended for outdoor use only. Not NSF certified.

Shaded models designed for use with drip systems.

Website [senninger.com](http://senninger.com) | Customer Support +1-407-877-5655

The Senninger commitment to world-class products, local support and technical expertise ensure we provide the most efficient and reliable agricultural irrigation solutions available in the world today.

  
Steve Abernethy, President of Senninger Irrigation