

Mechanized Irrigation

LOW PRESSURE - HIGH PERFORMANCE



AGRICULTURAL IRRIGATION | A Hunter Industries Company
Learn More. Visit senninger.com

Senninger[®]

Mechanized Irrigation



WOBBLEERS®



Flow: 0.80 - 18.35 gpm
Pressure: 10 - 15 psi
Droplet Size: Medium

Flow: 2.24 - 18.35 gpm
Pressure: 10 - 15 psi
Droplet Size: Small

Flow: 0.80 - 18.35 gpm
Pressure: 10 - 15 psi
Droplet Size: Medium

Flow: 3.24 - 18.35 gpm
Pressure: 10 - 15 psi
Droplet Size: Large

Xi-Wob (blue)

Xi-Wob (black)

Xi-Wob (grey)

Xi-Wob TOP (white)

Xcel-Wobbler TOP



Flow: 1.09 - 15.78 gpm
Pressure: 10 - 15 psi
Droplet Size: Medium

Flow: 2.24 - 15.78 gpm
Pressure: 10 - 15 psi
Droplet Size: Large

Flow: 2.24 - 15.78 gpm
Pressure: 10 - 15 psi
Droplet Size: Small

Flow: 2.24 - 12.88 gpm
Pressure: 10 psi
Droplet Size: Medium

Flow: 0.80 - 14.98 gpm
Pressure: 10 psi
Droplet Size: Large

LDN®

LDN - Spray

LDN - LEPA Bubbler

LDN - LDN Shroud

LDN - Part Circle



Flow: 0.27 - 21.18 gpm
Pressure: 6 - 20 psi

Flow: 0.27 - 21.18 gpm
Pressure: 6 - 15 psi
Several deflector pad options

Flow: 0.27 - 18.35 gpm
Pressure: 6 - 15 psi
Several deflector pad and insert options

Flow: 0.62 - 10.35 gpm
Pressure: 6 - 15 psi

SPRAYS

Super Spray®

End Spray

Impact Sprinkler

Impact Sprinkler



Flow: 0.27 - 29.96 gpm
Pressure: 6 - 40 psi
Twenty-two deflector pad options

Flow: 8.1 - 48.9 gpm
Pressure: 10 - 25 psi

Flow: 1.87 - 36.0 gpm
Pressure: 30 - 60 psi

Single max flow: 20 gpm
Double max flow: 15 gpm per side

REGULATORS AND ACCESSORIES

PRL

PSR-2

PMR-MF

Truss Rod Hose Slings



Flow: 0.5 - 8 gpm
Pressure: 6 - 40 psi

Flow: 0.5 - 15 gpm
Pressure: 6 - 50 psi

Flow: 2.0 - 20 gpm
Pressure: 6 - 60 psi

Five color-coded truss rod sizes.
For use with 125-degree goosenecks.

Boom System

Ball Valve and Fittings

Magnum Weight & One Weight

Pressure Drop



For pivot towers and overhangs



Several Models Available



Fits Senninger and other
Manufacturers' Applicators



Regular and
Freeze proof
models.